

CLAIMS

What is claimed is:

1 1. A jogging structure for translating wiring connections from points in a first
2 grid to corresponding points in a second grid in a chip carrier module, the structure
3 comprising:

4 a first translation layer, coupled to the first grid, said first translation layer
5 translating the first grid in an x-axis direction; and

6 a second translation layer, coupled to said first translation layer, said
7 second translation layer for translating said wiring connections from the first grid in a y-
8 axis direction, said y-axis direction being orthogonal to said x-axis direction;

9 wherein said second translation layer is further coupled to the second grid.

1 2. The structure of claim 1, wherein:

2 the points within the first grid have a first pitch, said first pitch being
3 defined by a first distance between neighboring points in the first grid;

4 the points within the second grid have a second pitch, said second pitch
5 being defined by a second distance between neighboring points in the second grid; and
6 said second pitch is not an integral multiple of said first pitch.

1 3. The structure of claim 1, wherein:

2 said first translation layer further comprises a first plurality of signal
3 interconnects, said first plurality of signal interconnects each having a jog line elongated
4 along said x-axis direction; and

5 said second translation layer further comprises a second plurality of signal
6 interconnects, said second plurality of signal interconnects each having a jog line
7 elongated along said y-axis direction.

2 4. The structure of claim 3, wherein:
3 each of said jog lines in said first plurality of signal interconnects is
4 disposed between an upper via contact and a lower via contact in said first translation
5 layer; and
6 each of said jog lines in said second plurality of signal interconnects is
7 disposed between an upper via contact and a lower via contact in said second translation
8 layer.

1 5. The structure of claim 4, wherein:
2 each individual upper via contact in said first translation layer is in
3 electrical communication with a corresponding point in the first grid;
4 each individual lower via contact in said first translation layer is in
5 electrical communication with a corresponding upper via contact in said second
6 translation layer; and
7 each individual lower via contact in said second translation layer is in
8 electrical communication with a corresponding point in the second grid.
9 signal via in said first plurality of signal vias are in electrical contact with corresponding
10 individual signal vias in said second plurality of signal vias.

1 6. The structure of claim 5, further comprising:
2 a first plurality of power busses in said first translation layer, disposed
3 along said x-axis direction; and
4 a second plurality of power busses in said second translation layer,
5 disposed in said y-axis direction.

7. The structure of claim 1, wherein:

the first grid comprises a C4 grid; and

the second grid comprises a logic service terminal (LST) grid.

8. A module for an integrated circuit (IC) chip, the module comprising:

a first grid for receiving electrical connections from the IC chip; and

a redistribution layer for fanning said electrical connections received by

said first grid from said first grid to a second grid, said redistribution layer further comprising:

a first translation layer, coupled to said first grid, said first

translation layer translating said first grid in an x-axis direction; and

a second translation layer, coupled to said first translation layer,

said second translation layer for translating said wiring connections from said first grid in a y-axis direction, said y-axis direction being orthogonal to said x-axis direction;

wherein said second translation layer is further coupled to said

second grid.

9. The module of claim 8, wherein:

the points within said first grid have a first pitch, said first pitch being

defined by a first distance between neighboring points in said first grid;

the points within said second grid have a second pitch, said second pitch

being defined by a second distance between neighboring points in said second grid; and

said second pitch is not an integral multiple of said first pitch.

1 10. The module of claim 8, wherein:
2 said first translation layer further comprises a first plurality of signal
3 interconnects, said first plurality of signal interconnects each having a jog line elongated
4 along said x-axis direction; and
5 said second translation layer further comprises a second plurality of signal
6 interconnects, said second plurality of signal interconnects each having a jog line
7 elongated along said y-axis direction.

1 11. The module of claim 10, wherein:
2 each of said jog lines in said first plurality of signal interconnects is
3 disposed between an upper via contact and a lower via contact in said first translation
4 layer; and
5 each of said jog lines in said second plurality of signal interconnects is
6 disposed between an upper via contact and a lower via contact in said second translation
7 layer.

1 12. The module of claim 11, wherein:
2 each individual upper via contact in said first translation layer is in
3 electrical communication with a corresponding point in the first grid;
4 each individual lower via contact in said first translation layer is in
5 electrical communication with a corresponding upper via contact in said second
6 translation layer; and
7 each individual lower via contact in said second translation layer is in
8 electrical communication with a corresponding point in the second grid.

1 13. The module of claim 12, further comprising:
2 a first plurality of power busses in said first translation layer, disposed
3 along said x-axis direction; and
4 a second plurality of power busses in said second translation layer,
5 disposed in said y-axis direction.

1 14. The module of claim 8, wherein:
2 said first grid comprises a C4 grid; and
3 said second grid comprises a logic service terminal (LST) grid.

1 15. A method for implementing a wiring translation in chip carrier module
2 between corresponding points in a first grid and a second grid, the points in the first grid
3 defining a first plane and the points in the second grid defining a second plane, the second
4 plane lying substantially parallel to the first plane, the method comprising:
5 connecting the first grid to a first translation layer within the module, said
6 first translation layer translating the points in the first grid in a first direction; and
7 connecting a second translation layer between said first translation layer
8 and the second grid, said second translation layer translating the points in the first grid in
9 a second direction, said second direction being orthogonal to said first direction.

1 16. The method of claim 15, wherein:
2 said first translation layer is configured to include a first plurality of signal
3 interconnects, said first plurality of signal interconnects each having a jog line elongated
4 along said x-axis direction; and
5 said second translation layer is configured to include a second plurality of
6 signal interconnects, said second plurality of signal interconnects each having a jog line
7 elongated along said y-axis direction.

1 17. The method of claim 16, wherein:
2 each of said jog lines in said first plurality of signal interconnects is
3 disposed between an upper via contact and a lower via contact in said first translation
4 layer; and
5 each of said jog lines in said second plurality of signal interconnects is
6 disposed between an upper via contact and a lower via contact in said second translation
7 layer.

1 18. The method of claim 17, wherein:
2 each individual upper via contact in said first translation layer is in
3 electrical communication with a corresponding point in the first grid;
4 each individual lower via contact in said first translation layer is in
5 electrical communication with a corresponding upper via contact in said second
6 translation layer; and
7 each individual lower via contact in said second translation layer is in
8 electrical communication with a corresponding point in the second grid.
9 signal via in said first plurality of signal vias are in electrical contact with corresponding
10 individual signal vias in said second plurality of signal vias.

